



INTRA KA VAADA



 Loading area (2 690 mm x 1607 mm – 8.8 ft x 5.3 ft)



 52 kW (70 hp) power & best-in-class gradeability



Leaf spring suspension (5 leaves in the front & 8 in the rear)



 Electronic power-assisted steering (EPAS)



• Best-in-class fuel efficiency (Gear shift advisor + Eco switch)



• Rated payload of 1300 kg











SPECIFICATIONS	INTRA V30 BSVI
ENGINE	
Engine Capacity	4-cylinder, 1 496 cm³ DI engine
Max. Engine Output	52 kW @ 4 000 r/min (70 hp)
Max. Torque	140 Nm @ 1800 - 3 000 r/min
WEIGHT	
Gross Vehicle Weight	2 565 kg
Payload	1 300 kg
DIMENSIONS	
Wheel Base	2 450 mm
Overall Length	4 460 mm
Load Body (length x breadth)	2 690 x 1 607 mm (8.8 feet x 5.3 feet)
Min. Turning Circle Radius	5.25 m
STEERING	
Туре	Electronic power-assisted steering
SUSPENSION	
Type (Front & Rear)	Semi-elliptical leaf springs
No. of Leaves	Front - 5, Rear - 8
PERFORMANCE	
Max. Gradeability	37%
TYRES	
Tyre Size/Type	185 R14 LT (14" radial tyres)

TO KNOW MORE

TOLL-FREE NUMBER | 1800 209 7979

SMS# <INTRA> to **5616161**#SMS charges as per service provider

VISIT OUR WEBSITE www.intra.tatamotors.com

The illustrations and photographs may show accessories and items of optional equipment which are not part of the standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement. Terms & conditions apply.



